

OSYRIS DWY 4000



Metalworking



TOTAL

APPLICATIONS

- Solvent-based fluid for corrosion protection specifically developed to present:
 - superior water displacement capability
 - medium-term protection
 - short drying time.

SPECIFICATIONS

- **OSYRIS DWY 4000** complies with Standard ISO 6743/8 (1987) : REE category.

ADVANTAGES

- **OSYRIS DWY 4000** is specifically designed for corrosion protection in the metal processing industry.
- **OSYRIS DWY 4000** presents a superior water displacement capability.
- **OSYRIS DWY 4000** coats the metal surface with a thin, soft and non drying protective film.
- **OSYRIS DWY 4000** provides protection for about six months during indoor storage and for about two months during outdoor and sheltered storage.
- **OSYRIS DWY 4000** presents a short drying time.
- **OSYRIS DWY 4000** can be easily applied:
 - With a brush
 - By spraying
 - By immersion.
- **OSYRIS DWY 4000** can be easily removed with:
 - Diluted alkaline detergents
 - Solvents (liquid or vapour phase)
 - Mechanical treatments.

TYPICAL CHARACTERISTICS	METHODS	UNITS	OSYRIS DWY 4000
Aspect	-	-	Clear
Density (@ 15°C)	EN ISO 12185	kg/m ³	820
Flash Point	EN ISO 2719	°C	66
Viscosity (@ 40°C)	DIN 51562	mm ² /s	1.9
Thickness of film	-	µm	1.7

Above characteristics are mean values given as an information.

**TOTAL LUBRIFIANTS
INDUSTRIE**

04-08-2015 (supersedes 05-09-2014)

OSYRIS DWY 4000

1/1



This lubricant used as recommended and for the application for which it has been designed does not present any particular risk.

A material safety data sheet conforming to the regulations in use in the E.C. can be obtained from your local commercial adviser or down loaded from www.quick-fds.com.